
GOC

INTERACTIVE SMART BOARD

PRODUCT BROCHURE

SIZES (55"/65"/75"/85"/86"/98"/100"/110")





Special functions

4K


4k HD



Save the QR code



Multi-touch




Miracast



Remote meeting



whiteboard



Split Screen



HD Audio



zoom




腾讯会议
Tencent Meeting

Google Meet


webex™

slack




102° Wide-Angle
Capturing the Big Picture

Make the meeting more
convenient



High-Definition Imaging
Capturing Every Detail



Collaboration

Effortlessly share and manage your content for productive, interactive teamwork. High-definition visuals and immersive sound create a focused environment, helping you achieve more effective meeting outcomes.




Ideate

Use the web or your preferred apps with a flexible, feature-rich whiteboard that allows you to explore and refine your ideas.



Google certified Applications available

Certified by Google, allowing you access to official Google tools and services for seamless work directly on the interactive whiteboard.







Upload files easily


Sharing Effortless File Upload via QR Code

Scan a QR code with your phone to easily upload images, videos, and documents from your phone to the interactive flat panel, making sharing stable and quick.



Precision Touch Instant Response to Every Touch

High-precision touch for fluid writing and instant display. Add tables, images, and more with ease. Scan to save or share it's all intuitive.




Dynamic graphics

Vibrant and flexible—objects can be stretched, rotated, moved, copied, and their colors adjusted with a simple selection.



4K display UI offers
1.07 billion colors (10-bit)



Dual System Optional Switch
with Ease



Non-glare panel optimizes
visibility in all conditions



High-brightness withstands
ambient light




4K Ultra HD Mirror Screen Audio and Video Synchronization

GOC conference panel delivers a fresh screen mirroring experience, offering diverse mirroring options. Easily mirror screens wirelessly from small to large displays or between large screens. The 4K ultra-HD display enhances clarity for project discussions, file sharing, and presentations.



Multi-window Application One Screen for Multiple Uses Improves Efficiency

It enables multi-application display with flexible window resizing and supports 2-split and 4-split screen views. During team collaboration and discussions, there's no need to switch between apps. You can take notes on the whiteboard while reviewing content, ensuring efficient workflow.



Application Scenarios

The GOC Interactive Flat Panel stands out in product design, information security, and advanced performance configurations, meeting elevated standards for professional environments and setting a new benchmark for high-end meetings



Company meeting



Intelligent education



Medical use



Construction industry

SPECIFICATION SHEET - 86 INCH INTERACTIVE SMART BOARD

Product Model:	GOC TN86	
Type	Parameter	Specification
Open cell	Country of Origin	CHINA
	Country of Manufacture	CHINA
	Screen Size	86 Inch
	Panel Brand / Model	GOCTN86
	Resolution / Aspect Ratio	16:9/ 3840×2160 Pixels /4K
	Active Area	1428.48×803.52(mm)
	Backlight Type	Direct LED(DLED)
	Brightness	400cd/m2
	Contrast Ratio	4000:1
	Pixel Pitch	0.315(mm) (H) x 0.315(mm) (V)
	Response Time	6(MS)
	Viewing Angle	89 / 89 / 89 / 89
	Chromaticity Coordinate	X:0.283 +0.03 Y: 0.297±0.03
	Display Colors	10bits + FRC, 1.07G colors
	Panel Frame Rate	60Hz
	Color Gamut	72% (NTSC)
	Brightness Uniformity	Nine-grid 70% or more
	Life Time	100,000 Hrs.
	PCBA model	RK 3576
	CPU	Octa (8) Core / Processor Speed:2.1 GHz
	RAM and ROM	8GB RAM and 128GB STORAGE
	OPS	<small>Core i5 12th Gen, 2.0 GHz Base frequency (8GB RAM DDR 4/256 GB SSD /1TB)</small>
	Touch Surface	Tempered Glass MOH7 Standard with Explosion proof Glass
	Touch Technology	Infrared
	Touch Surface	Anti-Glare
	System Version	Android14
	Touch Mode	Multi Touch 20 in Android 20 in Windows OPS
	HDMI Input	1×front +2×rear
	HDMI Output	1×rear
	DP Input	1
	SPDIF	1×rear (optical socket)
	RS232	1
	TYPE C	1
	USB Universal Serial Bus	1×USB2.0 (front) +1 ×USB2.0 (rear) + 1×USB3.0 (front) +1 ×USB3.0 (rear)
	Touch-USB	1× (front) +2× (rear)
	Audio output (Earphone)	1×rear (LINE OUT)
	PC AUDIO IN	1×rear
	MIC IN	1×rear
	Ethernet Input	2× (RJ45 Input)
	WIFI Aerial	WiFi6 (2×2.4G built-in module, 2×5G built-in module, 1×Bluetooth2.1 5.1)
OPTICAL OUT	1	
TF Card	1	
Speaker	30W (2×15W)	
Power	Power Input	B
	Operation Consumption	<180 W
	Standby Consumption	<0.5 W
	LED Indicator Light Mode	Power on: Blue /Power off: Red
	Main Power Switch	YES
	Touch Active Area(mm)	0.2mm
	Interpolation resolution	32767 (W)×32767 (D)
	Input Method	Opaque body (e.g. finger, pen, etc.)
	Connector Type	USB3.0/UART
	Supply Voltage	5V(USB)
	Glass Thickness(mm)	T4
	Support System	Windows XP/7/8/8.1/10(/64Android、Linux、IOS、Chrome

	Touch Durability	Unlimited time
Speaker	Output Power	40W(20W*2)
	Number of microphones	8 Array - 2MICS
Assistant PCBA	Key Function	Eight key control ECO/POWER
	Camera	48MP With AI Features
Support/Stand	Tilt Angle	0 degree
	Movable Stand	Steel Frame, Powder Coated Stand with Wheel Lock
	Cabinet material	Aluminum alloy surface box, Hardware back cover
	Wall Mounting Hole	400×400mm_M8
Accessories	Complete Machine	1470×85×877mm
	HDMI Cable	×1
	USB Cable	×1
	Power Cord	1×B/T(1.5M/3P)
	Instruction Manual	1 x languages English
	Warranty Card	×1
	Remote Control	×1
	Pen	×2
	Wall Mounting Kit	×1
	Packing Size	1598×227×1022mm
Container Loading	Gross / Net (Kg)	Approximate gross weight: 40Kg/Net weight: 37Kg
Operation Environment Ⅰ	Storage Temperature	-20°C~60°C
	Operation Temperature	0°C~40°C
	Operation Humidity	10~90%RH
	Altitude	≤2000m
Certifications	3C	YES
	ISO9001	YES
	ISO14001	YES
	FCC	YES

AI Features:	Benefits
Circled Selection for Image and Text Recognition	Identify images and text through circled selection.
Real-time Translation	Online mutual translation between multiple languages.
Video Assistant:	Automatically add subtitles and generate video summaries.

GESTETNER OF CEYLON – OUR CUSTOMER SERVICE COMMITMENT

- Response times - During standard working hours (8.30 am – 5.00 pm) 2 to 4 Hrs. for Colombo & Suburb (within 30km)
- Other Province (more than 30km) 6 to 8 Hrs.
- Resolution times - The Gestetner Ceylon will always endeavor to resolve problems as swiftly as possible depending on the nature of issue
- Central Call Center - Any Issue will be operated from Colombo with a Centralized Customer Inquiry Management System. All calls will be routed to the Centralized Call Center and will be monitored until the job is closed. E-mail: samson@gestetnersl.com
- Workshop facilities - The GOC Central Workshop facility is a full-fledged workspace with advanced technology and qualified Technicians Island wide.

Hotline: +94743221396 +94 112323 826 / +94 114725 500